



OVATION[®]

Exterior 100% Acrylic Semi-Gloss OV0012000 Series

CHARACTERISTICS

Ovation[™] Exterior is a Paint & Primer in One with a 100% acrylic formula for extra protection from cracking, peeling, & blistering. This product has great coverage and durability with Smooth Glide technology and has a low temp application to 35 degrees.

This **HGTV HOME by Sherwin-Williams** product provides a durable, mildew resistant coating for use on properly prepared wood, masonry, concrete, block, and metal.

Color: Most colors

Coverage: 250 - 400 sq ft/gal
@ 6.4-4 mils wet; 2.5-1.6 mils dry

Drying Time, @ 50% RH:
@ 35-45°F @ 45-90°F

Touch: 2 hour 1 hour

Recoat: 24-48 hours 4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

Finish: 35-45 units @ 60°

Flash Point: N/A

Tinting with Novocolor[™]:

Base	oz/gal	Strength
------	--------	----------

Extra White	0-6	100%
-------------	-----	------

Deep Base	10-12	100%
-----------	-------	------

Ultradeep	12-14	100%
-----------	-------	------

Vehicle Type: Acrylic

OV0012000

VOC (less exempt solvents):

<50 g/L; <0.42 lb/gal

As per 40 CFR 59.406 and SOR/2009-264, s. 12

Volume Solids: 37.53 ± 2%

Weight Solids: 47.08 ± 2%

Weight per Gallon: 9.82 lb

Mildew Resistant

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

SPECIFICATIONS

Aluminum & Aluminum Siding¹, Galvanized Steel¹, Steel, Vinyl Siding

2 cts. Ovation[®] Exterior Paint & Primer

Brick, Concrete Block, CMU

1 ct. Of an appropriate primer or filler

2 cts. Ovation[®] Exterior Paint & Primer

Cement Composition Siding/Panels

1 ct. Of an appropriate primer

2 cts. Ovation[®] Exterior Paint & Primer

Stucco, Cement, Concrete

1 ct. Of an appropriate primer

2 cts. Ovation[®] Exterior Paint & Primer

Wood, Plywood/Composition Board

1 ct. Of an appropriate primer

2 cts. Ovation[®] Exterior Paint & Primer

Wood (Cedar, Redwood)³

1 ct. Of an appropriate stain-blocking primer

2 cts. Ovation[®] Exterior Paint & Primer

1 On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher.

2 Not for use at temperatures under 50°F. See specific primer label for that product's application conditions.

3 Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. For best results on these woods, use a coat of stain-blocking primer.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or damaged paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Caulk around windows, doors, and other openings after spot priming bare surfaces with Ovation[®] Exterior Paint & Primer.

Aluminum and Galvanized Steel

Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, steel wool, or other abrading method.

Cement Composition Siding/Panels

Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 8, prime with an appropriate primer.

Wood, Plywood, Composition Board

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed.



OVATION[®]

Exterior 100% Acrylic Semi-Gloss OV0012000 Series

SURFACE PREPARATION

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with an appropriate masonry primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant. For extremely porous surfaces, a coat of block filler may be required to achieve a pinhole free film.

Steel

Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.

Stucco

Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 5-7 days and prime with masonry primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.

Vinyl

Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly.

Caulking

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes.

SURFACE PREPARATION

protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

APPLICATION

When the air temperature is at 35°F, substrates may be colder; prior to painting, check to be sure the **air, surface, and material temperature** are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 2-3 hours.

Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours.

No reduction necessary.

Brush

Use a nylon/polyester brush.

Roller

Use a 3/8" - 3/4" nap synthetic cover.

Spray—Airless

Pressure..... 2000 psi

Tip..... .015"-.019"

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment.

Follow manufacturer's instructions when using mineral spirits.

Do not pour unused contents down the drain. Consult with local authorities for proper methods of disposal and recycling.

CAUTIONS

For exterior use only
Protect from freezing.
Non-photochemically reactive.

LABEL CAUTIONS

CAUTION contains CRYSTALLINE SILICA and ZINC. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

HOTW 011/25/2014 OV0012001 24 47

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.