



OVATION®

Interior Vinyl Acrylic Semi-Gloss

OV0022000 Series

CHARACTERISTICS	SPECIFICATIONS	SURFACE PREPARATION
<p>Ovation® Interior Paint and Primer with ScrubSure Technology was formulated to be extremely scrubbable and stands up to repeated washing and scrubbing. It's smooth glide formula provides great coverage with minimal brush and roller marks. This ultra durable Paint and Primer in One will keep your home looking beautiful.</p> <p>This HGTV HOME by Sherwin-Williams product is recommended on properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.</p> <p>Color: Most colors Coverage: 400 sq ft/gal Drying Time, @77°F, 50% RH: Touch: 1 hour Recoat: 4 hours Drying and recoat times are temperature, humidity, and film thickness dependent Finish: 25-35 units @ 60° Flash Point: N/A Tinting with Novocolor™ : Base oz/gal Strength Extra White 0-6 100% Deep Base 10-12 100% Ultradeep 12-14 100% Vehicle Type: Vinyl Acrylic OV0022000 VOC (less exempt solvents): <50 g/L; <0.42 lb/gal As per 40 CFR 59.406 and SOR/2009-264, s.12 Volume Solids: 40 ± 2% Weight Solids: 53 ± 2% Weight per Gallon: 10.6 lb <p>Mildew Resistant This coating contains agents which inhibit the growth of mildew on the surface of this coating film.</p> </p>	<p>Drywall, Plaster, Wood 2 cts. Ovation® Interior Paint & Primer or 1 ct. Of an appropriate primer 2 cts. Ovation® Interior Paint & Primer</p> <p>Masonry, Concrete, Cement, Block (Can be filled to provide a smooth surface or primed if the substrate has a high pH) 1 ct. Of an appropriate primer 2 cts. Ovation® Interior Paint & Primer</p> <p>Ovation® Interior Paint & Primer can be used directly over existing coatings, or bare drywall, plaster and masonry (both with a cured pH of less than 9) and non-bleeding wood.</p> <p>When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.</p>	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or damaged paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Caulk around windows, doors, and other openings after spot priming bare surfaces with Ovation® Interior Paint & Primer.</p> <p>Drywall Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.</p> <p>Plaster Base plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon water. Repeat until the surface is hard, rinse with clear water and allow to dry.</p> <p>Wood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p>



OVATION®
Interior Vinyl Acrylic
Semi-Gloss
OV0022000 Series

<u>SURFACE PREPARATION</u>	<u>SURFACE PREPARATION</u>	<u>CAUTIONS</u>
<p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the suppliers recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with an appropriate primer.</p>	<p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p>	<p>For interior use only. Protect from freezing. Non-photochemically reactive.</p>
<p>Caulking Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.</p>	<p>APPLICATION Apply at temperatures above 50°F. No reduction necessary.</p> <p>Brush Use a nylon/polyester brush. Roller Use a 1/4" - 3/4" nap synthetic cover. Spray—Airless Pressure..... 2000 psi Tip017"- .021"</p>	<p>LABEL CAUTIONS CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</p> <p>HOTW 01/25/2014 OV0022001 24 47</p>

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.